

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (previously presented): A method for quantitation of surface-binding optical resonance profiles comprising, in combination, the steps of:

obtaining at least one calibration result from a calibration scan of at least one Region of Interest;

generating, from at least one calibration result, a calibration profile for at least one scanned Region of Interest;

obtaining at least one experimental result from an experimental scan of at least one Region of Interest; and

determining at least one resonance parameter by fitting at least one experimental result to the calibration profile,

wherein the calibration scan is performed at a high scan point density compared to the scan point density of the experimental scan.

Claim 2 (original): The method of claim 1, wherein one resonance parameter is an angle shift.

Claim 3 (original): The method of claim 1, wherein one resonance parameter is a wavelength shift.

Claim 4 (original): The method of claim 1, further including the step of storing at least one calibration profile in memory.

Claim 5 (original): The method of claim 1, further including the step of storing at least one resonance parameter in memory.

Claim 6 (original): The method of claim 1, further comprising the step of computing at least one calibration set statistic.

Claim 7 (original): The method of claim 6, further including the step of displaying at least one calibration set statistic.

Claim 8 (original): The method of claim 1, wherein said step of generating a calibration profile for at least one scanned Region of Interest comprises the steps of:
generating a raw calibration profile; and
determining at least one derivative of said calibration profile from the raw calibration profile.

Claim 9 (original): The method of claim 8, wherein said step of generating a

calibration profile for at least one scanned Region of Interest further comprises the step of smoothing said raw calibration profile.

Claim 10 (original): The method of claim 8, wherein said step of generating a calibration profile for at least one scanned Region of Interest further comprises the step of determining at least one property of said calibration profile from the raw calibration profile.

Claim 11 (original): The method of claim 10, wherein the properties determined are selected from the group consisting of Full Width at Half Maximum, nominal resonance angle, fractional depth, and maximum intensity.

Claim 12 (original): The method of claim 9, wherein said step of generating a calibration profile further comprises the step of subsampling the smoothed raw calibration profile.

Claim 13 (original): The method of claim 12, wherein said step of generating a calibration profile further comprises the step of extrapolating the ends of the subsampled smoothed raw calibration profile.

Claim 14 (original): The method of claim 13, wherein said step of generating a calibration profile further comprises the step of performing a second smooth of the

subsampled smoothed raw calibration profile.

Claim 15 (original): The method of claim 14, wherein said step of generating a calibration profile further comprises the step of storing the calibration profile in memory.

Claim 16 (original): The method of claim 15, wherein said step of generating a calibration profile further comprises the steps of:

determining the quality of the calibration profile; and
marking the calibration profile according to the quality determination.

Claim 17 (original): The method of claim 1, further including the step of performing a preliminary quality check on at least one calibration result.

Claim 18 (original): The method of claim 17, further including the step of flagging at least one calibration result in memory as valid or invalid according to the results of the preliminary quality check.

Claim 19 (original): The method of claim 1, further including the step of computing a derivative of at least one calibration profile.

Claim 20 (original): The method of claim 1, further including the step of displaying at

least one scan result to a user.

Claim 21 (original): The method of claim 1, wherein said step of determining at least one resonance parameter for said experimental scan of at least one Region of Interest comprises the steps of:

- calculating an estimated resonance shift;

- calculating at least one interpolated profile from said estimated resonance shift and said calibration profile;

- fitting said experimental scan, using said interpolated calibration profile;

- obtaining fit coefficients from said step of fitting;

- calculating, from the fit coefficients, a residual resonance shift from the resonance shift;

- calculating an improved estimate of the resonance shift; and

- iterating until the value of the resonance shift converges to a predetermined convergence criterion.

Claim 22 (original): The method of claim 21, wherein said step of determining at least one resonance parameter for said experimental scan of at least one Region of Interest comprises the step of calculating fit residuals.

Claim 23 (original): The method of claim 21, wherein said step of determining at least one resonance parameter further includes the step of estimating the time of scan

minimum.

Claim 24 (original): The method of claim 23, wherein said step of determining at least one resonance parameter further includes the step of initially pruning the experimental scan to within the limits of the calibration profile.

Claim 25 (original): The method of claim 24, wherein said step of determining at least one resonance parameter further includes the step of fitting to a sweet zone, comprising the steps of:

- truncating the interpolated profile to the sweet zone; and
- redetermining the resonance parameter utilizing the truncated interpolated profile.

Claim 26 (original): The method of claim 25, wherein said step of determining at least one resonance parameter further includes the step of performing initial data validity checks.

Claim 27 (original): The method of claim 26, wherein said step of performing initial data validity checks comprises the steps of:

- checking profile availability;
- checking self-consistency of data; and
- checking scan indexing.

Claim 28 (original): The method of claim 21, wherein said step of fitting employs a least squares fit.

Claim 29 (original): The method of claim 1, further including the step of reporting errors in an error log.

Claim 30 (original): The method of claim 29, wherein the step of reporting errors utilizes a local error log.

Claim 31 (original): The method of claim 29, wherein the step of reporting errors employs remote error reporting.

Claim 32 (original): The method of claim 1, further including the step of performing a chip qualification check.

Claim 33 (previously presented): A method for quantitation of surface-binding optical resonance profiles comprising, in combination, the steps of:

obtaining at least one calibration result from a calibration scan of at least one Region of Interest;

generating, from at least one calibration result, a calibration profile for at least one scanned Region of Interest, comprising the steps of:

- generating a raw calibration profile;
- smoothing said raw calibration profile;
- subsampling the smoothed raw calibration profile; and
- determining properties of said calibration profile from the smoothed raw calibration profile;
- storing at least one calibration profile in memory;
- computing a derivative of at least one calibration profile;
- obtaining at least one experimental result from an experimental scan of at least one Region of Interest;
- determining a resonance shift of at least one experimental result relative to at least one calibration profile, comprising the steps of:
 - calculating an estimated resonance shift;
 - calculating at least one interpolated profile from said estimated resonance shift and said calibration profile;
 - fitting said experimental scan, using said interpolated calibration profile;
 - obtaining fit coefficients from said step of fitting;
 - calculating, from the fit coefficients, a residual resonance shift from the resonance shift;
 - calculating an improved estimate of the resonance shift;
 - calculating fit residuals;
 - iterating until the estimated value of the resonance shift converges to a

predetermined convergence criterion; and
estimating the time of scan minimum; and
displaying at least one scan result to a user,
wherein the calibration scan is performed at a high scan point density
compared to the scan point density of the experimental scan.

Claims 34-46 (cancelled)